VOLUME 8 ISSUE 9

SEPTEMBER 2011

3331 NW 55th Street

Cape Coral, FL





Don't Reroof It

"Up On Top" News

SERVICE WORKS YOUR FULL SERVICE ROOFING CONTRACTOR

What To Look For In Roof Maintenance

flat roof, the roof the elements. Routine preven-roof. tive roof maintenance can protect buildings from damaging If roof maintenance has been building life-cycle costs.

The trained eye can spot prob- openings in the roof system. lems on the roof surface. Simple visual inspection can re- Check for cracked or missing veal obvious signs of problems. caulk at walls and around pene-

that overhang a roof should be for loose or missing fasteners. trimmed or cut back to reduce the potential for tree debris If the roof is a shingle syson the roof.

debris should immediately be corrosion. removed. When inspecting guting properly.

Whether a building has a steep- checked to ensure that they slope, low-slope, or even a have not de-bonded from the is the base material or deteriorated first line of defense against to the point of exposing the

weather, extend the life of the deferred for an extended period roof system, and decrease of time, vegetation may grow on the roof and damage the membrane and flashings and create

trations. Pitch pockets should Roofs should be checked for de- be filled with pourable sealer bris and sharp items that could to the top of the pocket with damage the roof system. Sharp no cracks in the sealer. Peitems should be removed from rimeter sheet metal should be roof immediately. Trees secured to the substrate. Look

tem, check for missing or damaged shingles. Damage includes Ensure drain covers are prop-splitting or cracking of the erly installed to prevent de-shingles and curling of the bris from clogging drain lines, edges and loss of aggregate and make sure scupper openings surfacing on asphalt shingles. are clear of debris. If the Associated metal components, roof has gutters and down-such as ridge vents and hot spouts, they should be in-stacks, should be checked for spected and, if clogged, the openings, damage, and surface

ters, check for sagging, which Repair work should be performed will prevent water from drain- by qualified roofing personnel and in accordance with guidelines established by the Coatings on the roof membrane roof system manufacturer and and flashings should also be the National Roofing Contractors Association (NRCA).